

Features

- Oilless
- Simple Installation
- Quiet Operation
- Low Maintenance
- Compatible with oxygen



Class 1 Inc. simplex, oilless, rotary vane vacuum pump, factory assembled and tested, as follows:

Model: OLRV75-RXXX1
Capacity: 2.0 SCFM @ 20" Hg [57 l / min]
Maximum end vacuum: 25" Hg
Electrical: .6 HP, 120V, 1 Phase, 60 Hz [optional 230V / 1 / 60]

Vacuum Pump: Becker single stage, direct-driven, oilless, air-cooled, rotary vane vacuum pump complete with:

- high strength carbon graphite composite sliding vanes
- shaft driven cooling fan, and air shroud for pump cooling
- integral close-coupled TEFC motor
- 5 μ inlet filter with replaceable element, inlet bleed valve, and 63.5 mm liquid filled vacuum gauge
- mounting flange

Piping: One 1/2" 316L stainless steel flexible inlet connector

Control: Motor-rated On / Off toggle switch suitable for wall mounting by others

Features

- Oilless
- Simple Installation
- Quiet Operation
- Low Maintenance
- Compatible with oxygen



Class 1 Inc. simplex, oilless, rotary vane vacuum pump, factory assembled and tested, as follows:

Model: OLRV100-RXXX1
Capacity: 3.0 SCFM @ 20" Hg [85 l / min]
Maximum end vacuum: 25" Hg
Electrical: 1 HP, 120V, 1 Phase, 60 Hz [optional 230V / 1 / 60]

Vacuum Pump: Becker single stage, direct-driven, oilless, air-cooled, rotary vane vacuum pump complete with:

- high strength carbon graphite composite sliding vanes
- shaft driven cooling fan, and air shroud for pump cooling
- integral close-coupled TEFC motor
- 5 μ inlet filter with replaceable element, inlet bleed valve, and 63.5 mm liquid filled vacuum gauge
- mounting flange

Piping: One 1/2" 316L stainless steel flexible inlet connector

Control: Motor-rated On / Off toggle switch suitable for wall mounting by others

Features

- Oilless
- Simple Installation
- Quiet Operation
- Low Maintenance
- Compatible with oxygen



Class 1 Inc. simplex, oilless, rotary vane vacuum pump, factory assembled and tested, as follows:

Model: OLRV150-RXXX1
Capacity: 4.7 SCFM @ 20" Hg [133 l / min]
Maximum end vacuum: 25" Hg
Electrical: 1.2 HP, 120V, 1 Phase, 60 Hz [optional 230V / 1 / 60]

Vacuum Pump: Becker single stage, direct-driven, oilless, air-cooled, rotary vane vacuum pump complete with:

- high strength carbon graphite composite sliding vanes
- shaft driven cooling fan, and air shroud for pump cooling
- integral close-coupled TEFC motor
- 5µ inlet filter with replaceable element, inlet bleed valve, and 63.5 mm liquid filled vacuum gauge
- mounting flange

Piping: One 3/4" 316L stainless steel flexible inlet connector

Control: Motor-rated On / Off toggle switch suitable for wall mounting by others